



**FST**

**Flame Spray Technologies**

**SEALER**

**THERMAL SPRAY CONSUMABLES GUIDE**

- Notes: **A.** For detail go to SprayTech **FST-TS-SEALERS**  
**B.** For shipment, please note that sealers are considered **Hazardous Good**

<b>SEALERS</b>			
<b>FST p/n</b>	<b>Type</b>	<b>Volume</b>	<b>Typical Properties</b>
<b>TS-Sealer D</b>	Standard Sealer	1 liter – 5 liter ½ Gallon (USA)	<ul style="list-style-type: none"> <li>• HVOF, APS, VPS, Arc, Flame</li> <li>• Porosity size (mm): 0-0,1</li> <li>• Temp. Resistance: -40/300°C</li> </ul>
<b>TS-Sealer P</b>	High Porosity Sealer	1 liter – 5 liter ½ Gallon (USA)	<ul style="list-style-type: none"> <li>• APS, Arc, Flame</li> <li>• Porosity size (mm): 0,1-0,5</li> <li>• Temp. Resistance: -40/300°C</li> </ul>
<b>TS-Sealer HT</b>	High Temp Sealer	1 liter – 5 liter ½ Gallon (USA)	<ul style="list-style-type: none"> <li>• HVOF, APS, VPS, Arc, Flame</li> <li>• Porosity size (mm): 0-0,1</li> <li>• Temp. Resistance: -40/500°C</li> </ul>
<b>TS-Sealer SR</b>	Solvent Resistant	1 liter – 5 liter ½ Gallon (USA)	<ul style="list-style-type: none"> <li>• HVOF, APS, VPS, Arc, Flame</li> <li>• Porosity size (mm): 0-0,5</li> <li>• Temp. Resistance: -40/200°C</li> </ul>
<b>TS-Sealer HS</b>	High Solid Body. Hot	1 liter – 5 liter ½ Gallon (USA)	<ul style="list-style-type: none"> <li>• HVOF, APS, VPS, Arc, Flame</li> <li>• Porosity size (mm): 0-0,5</li> <li>• Temp. Resistance: -40/200°C</li> </ul>

